

## **Port Powered, Anti-Streaming Device**

### **Model 3001**



The Model 3001 is an Anti-Streaming Device that monitors your communication line for streaming conditions caused by a malfunctioning terminal. Deriving power from the RS-232 interface, the Model 3001 requires no AC power or batteries. It can be connected directly to a terminal via a female DB-25 and to a modem or multiplexer via a male DB-25. The Model 3001 operates in point-to-point or multi-point environments and is transparent to data rate and format. It is housed in a sturdy ABS plastic case measuring only 2.2L x 2.1W x 0.7H in.

#### **Specifications:**

|                    |   |
|--------------------|---|
| Connectors:        | DB-25 Male on DCE side; DB-25 Female on DTE side            |
| DTE Interfaces:    | EIA RS-232-A, CCITT V.24                                    |
| Data Rates:        | Transparent to data   |
| Indicators:        | 4 LEDs monitor RTS (from DTE), TD, RD and the Timeout Alarm |
| Timeout Periods:   | 12.5, 25, 50, 400 seconds                                   |
| Temperature Range: | 0-50°C (32-122°F)   |
| Humidity:          | Up to 95% non-condensing                                    |
| Power Supply:      | None required; uses power from data and control signals     |
| Dimensions:        | 2.2L x 2.1W x 0.70H inches.                                 |
| Weight:            | 1.5 oz  |

B&B Electronics - September 1997

Phone: (815) 433-5100  
Office Fax: (815) 433-5105  
Tech Fax: (815) 433-5104  
Sales Fax: (815) 433-5109

**B & B electronics**  
**MANUFACTURING COMPANY**  
707 Dayton Road -- P.O. Box 1040 -- Ottawa, IL 61350 USA

Home Page: [www.bb-elec.com](http://www.bb-elec.com)  
E-mail: [orders@bb-elec.com](mailto:orders@bb-elec.com)  
[support@bb-elec.com](mailto:support@bb-elec.com)  
[catrqt@bb-elec.com](mailto:catrqt@bb-elec.com)